

LIL P



SPECIFICATIONS

LENGTH	38 FT
BREADTH	10 FT
DEPTH	4 FT
DRAFT	2 FT
PASSENGERS	10
SPEED	40 MPH
DECK SPACE	20FT X 10 FT

DESCRIPTION

The vessel is of all welded aluminum construction outfitted with twin 300 hp, V6, four stroke Yamaha Outboards with stainless steel propellers. Steering is hydraulic and Lenco Trim Tabs.

The vessel has an all welded aluminum cabin with an operator's control console located forward on the starboard side with a vinyl covered seat. The cabin has a forward and aft watertight doors and rubber gasket mounted weather tight windows. Cabin has vinyl bench seating to seat ten (10) passengers. The rood of the cabin is insulated and atop is mounted a 15.5 cabin type air conditioner. The interior is finished with fiberglass type paneling with wood trim. The cabin has interior lighting.

The square bow is fitted with approximately 4' high push knees one each port and starboard side. The push knees and between the push knees is faced with fabricated rubber bumpers.

Mid way on each port and side there is a 2" split pipe guard rail. At deck level there is also a 2" split pipe guard rail.

The operator's console is fitted with the engines controls, engines instruments, a Furuno VX2 Radar, a Furuno GPS instrument, a 2" compass, a Furuno Depth Reader, and (2) Standard VHF radios. There are two toggle/fused switch panels and a generator panel.

There is a remote control search light

There are three (3) Rule type bilge pumps

The cabin is cool with two (2) 15.5 BTU Air Conditioners

Located in the no. 3 compartment is a 6 KW raw water cooled Kubota diesel generator set

There is a built in tank with three compartments that will carry 350 gallon gas, 100 gallons of diesel fuel and 750 potable water

LIFE SAVING AND FIREFIGHTING EQUIPMENT:

There are dry chemical fire extinguishers with current inspection tags.

There are twelve (12) life preservers onboard

One (1) First aid kit onboard

One (1) Ring buoy with float light onboard

